

Replacement parts may no longer be available

MOTOROLA

STX Series

Parts List

REF.			REF.		ı	REF.		
N0.	PART NO.	DESCRIPTION	N0.	PART NO.	DESCRIPTION	N0.	PART NO.	DESCRIPTION
1		Plate, Escutcheon	46		PCB, PTT (not field	84		Insulator, LCD (not field
2	3205933J02	Seal, Switch (some models	10		replaceable; order item 45)	01		replaceable;
_	020000002	require only one)	47		Contact, Snap-Dome			order item 80 or 81)
3	0305941K04	Screw, Control Top, #4-40	77		(not field replaceable;	85		Elastomer, LCD (not field
J	0303341104	HEXBTN			order item 45)	00		replaceable;
4		Lockwasher, #4	48		Seal, Dome (not field			order item 80 or 81)
5	3205082E11	"O" Ring	40		replaceable; order item 45)	86		Bezel, LCD (not field
6	0105957K69	Lower Housing Kit (includes	49		Insulator, B+	00		replaceable;
U	0105557105	items 97 and 98)	51		Insulator, Logic – not available			order item 80 or 81)
7	6405473N01	Baseplate	52		Insulator, RF – not available	87		Display Board Kit w/ LCD/LED
8	5505727N01	Latch, Battery	53		Standoff (not field	0/		(not field replaceable;
9	4105944K01		33					
10	3905421C13	Spring, Latch	54		replaceable; order item 50)			order item 80)
	0305941K02	Contact, Battery Screw, Baseplate, #4-40	54 55	0305731J06	Screw, #2-56 PHLPAN Screw, #2-56 PHLPAN			Keyboard Kit w/o LCD/LED (not field replaceable;
11	3205082E24		56	NTN4519A	*			
12		"O" Ring	30	NIIN4515A	Rear Shield Kit (includes	00		order item 80)
13	4605945K03 0400002625	Bushing, B+	F-7		item 57)	88		Light Pipe, LCD (not field
14		Lockwasher, #2	57	0000000000	Insulator, Rear – not available	00		replaceable; order item 80)
16	0705830C02	Support, Contact	58	2605723N01	Shield, Front	89		Shield, Static (not field
17	0300138651	Screw, #2-56 x 1/8" PHLPAN		NTN5646B	Front Shield Kit	00		replaceable; order item 80)
18	3205082E11	"O" Ring		F00F007 100	(includes items 59-63 and 100)	90		Keypad, 3-Key (not field
19		Contact, B+	59	5005227J02	Microphone (see Transceiver			replaceable; order item 80)
20		Upper Housing Kit w/o Rotary	00	44054778104	Board Parts List), (MK501)			Keypad, 15-Key (not field
		Switch (includes items 34	60	1105477N01	Adhesive, Speaker			replaceable; order item 80)
		and 94-96)	61	5005269T03	Speaker, Transducer, 8 ohms,			Keypad, 12-Key (not field
		Upper Housing Kit w/ Rotary			LS501	0.4		replaceable; order item 80)
		Switch (includes items 34	62		Boot, Microphone	91	4505369Q01	Lever, PTT
		and 94-96)	63	0905212P02	Connector, Speaker/Mic. (J2)	92	3205853H02	Gasket
21	0105952M69	RF Switch; Kit	65	4205474P01	Clip, B+	93		Pad, RF
		(includes items 22 and 106)	66	0905006P01	Plug, Coax, RF	94		Retainer, Membrane (not field
22	0405483P01	Washer, RF Jack	68	8405758N03	Interconnect, Display	0.5		replaceable; order item 20)
23	0205578M01	Nut, Stud	69	3305206P01	Label, Emergency	95		Membrane (not field
24	4305577M01	Stud		3305206P03	Label, Volume Set			replaceable; order item 20)
25	3205472P07	"O" Ring, Stud	70	3605295P01	Knob, Volume Switch	96		Grille, Upper Housing (not
26	3205639F03	Gasket	71	3605295P02	Knob, Subfleet Switch (used			field replaceable;
27	0300140383	Screw, #2-56 x 9/16" PHLPAN			only on Rotary Switch Models)			order item 20)
28	0205588M01	Nut, Antenna Seal	72	0305480E02	Screw, Set. #4-40 x 3/32"	97		Actuator, PTT (not field
29	0905771F02	Pin, Coaxial			(only one used on			replaceable; order item 6
31	3905698N01	Switch, Control			Non-Rotary Switch Models)	98		Retainer, PTT (not field
32	6405187P01	Plate, Control Switch	73		Screw, Front Cover			replaceable; order item 6)
33	0300136782	Screw, #2-56 x 3/16" PHLPAN	74	3205082E66	"O" Ring, Control-Top	99	1105668K35	Pad, Urethane
34		Bushing, Antenna (not field	75	3205082E67	"O" Ring, Front Cover	100		Insulator, Front — not available
		replaceable; Order item 20)	77	3205606P01	Seal, Side	101		Nut, Retainer
35	1505673C03	Connector, Side (J601)	78	0300136783	Screw, #2-56 x 5/16" PHLPAN	102	1405664J01	Insulator, Plunger
36	NAF4000B	Antenna, 800MHz Dipole	79	0300139444	Screw, #2-56 x 5/32" PHLPAN	103	4405829J01	Plunger, RF Switch
37		Control-Flex Kit w/o Rotary	80	RPX1020A	Plain Front Cover Kit	104	4105836J01	Spring, RF Switch
		Switch (includes items 38-42)			(includes items 82 and 83)	105	1405787C01	Insulator, Spring
38	0905675C01	Socket		RPX1021A	3-Key Front Cover Kit	106	0905006P02	Socket, Coax, RF (P4)
39	0905463Q01	Connector, 20-Pin (J1)			(includes items 81-90)	107	3205082E25	"O" Ring, Port
42	1805799P01	Potentiometer, (R601, Volume,		RPX1023A	12-Key Front Cover Kit	108		Seal, Port
		On/Off)			(includes items 82, 83, 87,	109	3205473P04	"O" Ring, Side Seal
43	RPX4689A	Switch, Subfleet (Optional)			89 and 90)	110	NTN5023A	Retainer, Side Seal
44	0200140458	Nut, Switch	82	1305954N01	Escutcheon, Front Cover, 3-Key			Screw, Captive 6-32 x .190
45		Frame Kit (includes items		1305954N03	Escutcheon, Front Cover, 15-Key	113		Pin, Stop
		46-49) – not available	83		Nut, Front Cover			

Cancelled Product STX Series: Aftermarket support criteria has been met for spare parts. Items may no longer be available.



STX Series



Portable Accessories

Chargers



Single Unit Chargers

They are capable of charging batteries while they are on or off of the radio. When the battery is fully charged, a visual indication is given (if it is a rapid charger) and the

charger automatically reverts to a trickle charge rate. Actual charging time varies directly with battery capacity

NLN8858A Rapid Charge, 117 Volt

Adapter Kit


NTN4529A Adapter Kit, for 6 Unit Charger (for wall or rack mount applications)

Battery Maintenance System Plus (BMS Plus)

Using interchangeable battery adapters (sold separately), the BMS^{plus} is capable of charging and discharging, analyzing, conditioning and cycle test on batteries; tracking battery voltage and capacity (mAh).

The BMS^{plus} offers a 3 year warranty. Its easy-to-use design supports hundreds of 2-way, cellular, and camcorder batteries with printer port* (Serial-RS-232C port – uses female 9-pin to male 25-pin cable).

WPLN4079BR Six-Station, 110V AC, 50/60 Hz **WPLN4080BR** Six-Station, 230V AC, 50/60 Hz



WPLN4079BR

BMX^{plus} Adapter

TDN9451A Standard Adapter, STX

Battery Optimizing System II (BOS II)



WPLN4124AR

No other battery analyzer matches the speed, accuracy, and versatility of the Battery Optimizing System II. Ideal for large fleet, public safety, and all other users who rely on their battery performance. Now with increased power, more sophisticated programming options, and easier to use navigation paths, optimizing your batteries was never easier. Key features include:

- Support for NiCd, NiMH, Li-ion, and SLA batteries
- 100 watt power supply and programmable from 100 mAH to 4 amps per station
- Interchangeable adapters accomodate all major brands
- Includes a variety of user programs and allows for customizable programming
- Proprietary recondition cycle restores NiCd and NiMH batteries
- Increased processing power and testing resolution including a three minute Quicktest that measures the batteries State of Health (SoH)
- Printer output for reports and labels
- Three year warranty

WPLN4124AR BOS II, Four-Station, 100-240V AC (US line cord) **WPLN4125AR** BOS II, Four-Station, 100-240V AC (UK/Euro line cords)

BOS II Adapter

RL-71223 Standard Adapter

^{*} Compatible with the STAR Micronics SP200 series printers, available from any STAR Micronics distributor, and other printers with STAR emulation.





Motorola Conditioning Charger (MCC)

The MCC will help extend battery life and enhance battery operation. It will safely condition and charge your specified Nickel Cadmium (NiCd) and Nickel Metal Hydride (NiMH) batteries in approximately one to two hours.



WPPN4002BR 110V AC Base Charge Unit only

WPPN4006AR 220V AC Base Charge Unit only

WPPN4000BR 7 Volt Adapter only

WPLN4098AR MCC Kit, 110V AC; includes both base unit and 7V adapter

WPLN4099BR MCC Kit, 220V AC; includes both base unit and 7V adapter

3080384G15 Cigarette Lighter Adapter Cord

RLN4814A Mounting Bracket for Motorola single unit conditioning chargers

MCC Multi-Unit Conditioning Charger

WPPN4065BR Four-station Base, 110V. (Order adapter plates separately)



Carrying Accessories

NTN4968A

Carrying Cases

A variety of carrying accessories are available for your comfort and convenience. The carrying cases are available in sizes designed to fit your radio & battery and permit audio to be heard clearly.

Swivel Carry Cases

NTN4968A Leather Carry Case and Swivel Belt Loop Holder, For Medium Capacity Battery (Order Velcro T-strap separately)



NTN4350A

NTN4969A Leather Carry Case and Swivel Belt Loop Holder, For High Capacity Battery (Order Velcro T-strap separately)

Carry Holder

NTN4350A Plastic Carry Holder with Belt Loop, for all models







Carrying Accessories



Full Cover

NTN4971A Full Cover, Velcro, For All Models



Belt

4200865599 1.75" Wide Leather Belt, For All Models







Carrying Strap NTN5243A Carrying Strap,
For All Models

NTN5243A

Belt Loop

4205857B01 Belt Loop, for Swivel Case, 2"

4282421J06 Swivel Belt Loop, 2.5"

Carrying Accessories



Remote Speaker Microphone

Remote speaker microphones allow the user to talk and listen without removing the radio from its carry case or carry holder. It has a top-ported speaker for improved audio reception and audio input.

NMN6176A Remote Speaker Microphone with Coil Cord, Clip Back, 2.5 mm Earpiece Jack and Earpiece (NTN4742A)

NMN6177A Remote Speaker Microphone with Coil Cord and Clip Back

Public Safety Remote Speaker Microphone

This microphone is very similar to the remote speaker microphones, as it is weatherized, and has the top-ported speaker for better audio. There is an antenna for improved coverage.

NMN6175A Public Safety Remote Speaker Microphone, with Clip Back, 800-900MHz Antenna Included

8505241U06 Antenna





Epaulet Strap Black leather enau

Black leather epaulet straps secure remote speaker microphone to epaulet of shirts or jackets and attach around cord.

RLN4294A Epaulet Strap, Velcro

RLN4295A Epaulet Strap, Small Clip

NTN4664A Three wire surveillance accessory with earpiece, microphone, and push-to-talk as separate pieces.

NTN4742A Earpiece without Volume Control







Audio Accessories

Ear Microphone System

This compact unit picks up the voice through bone vibrations in the ear canal. Ideal for use in high noise environments. Available in PTT or Voice-activated (VOX) capabilities for total hands free communications. Order Interface Module separately.



Ear Microphones

BDN6677A Ear Microphone for Standard Noise Levels (up to 95 dB), Black

BDN6678A Ear Microphone for Standard Noise Levels (up to 95 dB), Beige

BDN6641A Ear Microphone for High Noise Levels (up to 105 dB), Grey



BDN6644B Push-To-Talk Interface Module



Ear Microphone Optional Accessories

0180300E25 Earguard with Adjustable Loop

0180358B38

Remote Push-To-Talk Ring Switch

0180358B32 Earholder, Black, Size Small

0180358B33 Earholder. Black, Size Medium





0180358B34 Earholder, Black, Size Large 0180358B35 Earholder, Clear, Size Small 0180358B36 Earholder, Clear, Size Medium 0180358B37 Earholder, Clear, Size Large

Audio Accessories

Ear Microphone Accessories (cont'd)

4280369E44 Replaceable Belt Clip with Screws

5080358B28 Eartips, Black, Size Medium (10 per pack)


5080358B29 Eartips, Black, Size Large (10 per pack)

5080358B30 Eartips, Beige, Size Medium (10 per pack)

5080358B31 Eartips, Beige, Size Large (10 per pack)

Ear Mics

Single unit microphone and speaker worn in the ear. Eliminates the need for handheld microphones or conventional headsets. Compact, rugged design allows





0180359A42 Interface Cable for STX

0180359A51 Optional PTT Ring Switch for

RMN4001B

0180356B97 Optional PTT Ring Switch for RMN4001B Only



0180359A51







Audio Accessories

HMN1015A Remote Microphone

TAF6041A 806-866MHz Roof Top Antenna



Headsets

All headset accessories include adapter cables and can be plugged directly into radio. No additional equipment is required.

Low to moderate noise level (less than 100 dB) lightweight headset with Electret condenser microphone and single speaker. *NOTE: Cannot be worn with headgear.*

BDN6350A In-line push-to-talk switch

BDN6356A Body/foot switch that can be belt mounted

BDN6358A In-line push-to-talk switch

High noise level headset (up to 115 dB) with noise cancelling microphone and dual speaker. *NOTE: for use with respirator or face mask kit.*

BDN6314A Body/foot switch that can be belt mounted

Audio Accessories

High noise level headset (up to 125 dB) with noise-cancelling microphone and push-to-talk switch located on earcup. Vox module contained within headset on voice activated units. Factory Mutual Approved. *NOTE: Can be worn with or without hardhat or fire helmet.*

BDN6645A Push-To-Talk Headset with Boom Microphone, Requires Adapter Cable.



BDN6635B Voice-Activated Headset with Boom Microphone, Requires Adapter Cable, Includes 110V Charger



BDN6636B Voice-Activated Headset with Throat Microphone, Requires Adapter Cable, Includes 110V Charger

BDN6636B (Shown with adapter cable BDN6638A)

0180357B05 Spare VOX Headset Charger 110V

BDN6638A Adapter Cable for BDN6635, BDN6636 and BDN6645

6881126E79 Instruction Manual for BDN6645A

6881126E78 Instruction Manual for BDN6635 and BDN6636 Headsets

8/03





MOTOROLA

Portable Accessories, Batteries

Audio Accessories

Helmet Kits



The following DO NOT include headgear. NOTE: All helmet and face mask kits require a radio cable assembly (order separately).

Industrial/Police helmet kits for Bullard (Industrial) headgear with military noise cancelling microphone.

BDN6275A Single Speaker

Bell BT400 (Police) full coverage headgear with military noisecancelling microphone (cable assembly required, order separately)

BDN6362A Single Speaker (Police) **BDN6363A** Dual Speaker (Police)

Cable Assemblies

NOTE: All helmet kits require one of the following cable assemblies:

BDN6315A Cable assembly for Police Radio helmet kit with transmit switch, volume control, microphone electronics and a push-to-talk jack built into a belt mounted control box

BDN6292A Cable assembly for Police Radio helmet kit with handlebar push-to-talk switch for belt mounted control box (only applies to BDN6315A)

Portable Batteries

Nickel-Cadmium Premium

Part Number: NTN4326A

Volts: 7.5 Avg. mAh: 1300 Height: 2-7/16" Intrinsically Safe: No



NTN4326A

Part Number: NTN4327C

Volts: 7.5 Avg. mAh: 1800 Height: 3-11/16" Intrinsically Safe: No



NTN4327C

Part Number: NTN4500A

Volts: 7.5 Avg. mAh: 1800 Height: 3-11/16" Intrinsically Safe: Yes



NTN4500A

Part Number: NTN4534A

Volts: 7.5 Avg. mAh: 1300 Height: 2-7/16" Intrinsically Safe: Yes



NTN4534A







Antennas, Tools, Service Aids

Portable Antennas

Dipole Antennas

Dipole molded antennas are injection molded in lasting polyurethane. The wide skirt at the bottom of the connector protects against damaging environmental elements. The dipole antenna is ideal when strong and solid signal clarity is demanded.

NAF4000B

Dipole, 806-869MHz, 8"

Flexible Whip Antenna

Flexible Whip antennas have a one-piece finish and steel core for optimal radiation characteristics. Provides more comfort when radio is worn on the belt.

8505241U03

Flexible Whip, 806-870MHz, 7"

Stubby Antenna

This stubby quarterwave antenna is ideal when radio is worn on the belt because the short antenna is non-obtrusive.

*8505241U06

Stubby, 806-941MHz, 4"





Alignment Tools

Tuning Tools

6605106N01 Tuning Tool, Adjusts Squelch Threshold

6605147J01 Tuning Tool, for Potentiometers, Local Oscillator Coil, Quad Detector

6605106N01

Service Aids

Battery Block Adapter

Transceiver can be connected to the battery eliminator with this adapter, so it remains functional when out of the radio.

RTL4206A Battery Block Adapter



RTL4206A

^{*8505241}U06 is a broad band antenna that operates in the 800/900MHz band





Service Aids, Manuals

Service Aids

RF Adapter Cable

Control the radio locally while taking transmitter measurements by attaching this adapter to the universal side connector.

RTK4087A RF Cable Adapter



Radio Test Cable

Used with RTX4005 Portable Radio Test Set for transmitter, receiver alignment and performance checks.

RTK4006A Test Cable

SMA to BNC Adapter

Make transmitter measurements while the portable is connected to the portable test set. The adapter connects the antenna jack.

5880384G68 RF Adapter

Manuals

STX Series

6881040C25 Models H25/35TJB5170AN, H25/35TJC5170AN,

H25/35STC5170AN,H25/35STD5170AN, H25/35STE5170AN Service Manual

6881041C65 Model N1352A Instruction Manual

6881069C65 Models H25STC/D/E, H25TJB/C, H35STC/D/E,

H35TJB/C Theory/Maintenance Manual

6881049C90 SMARTNET Operating Instructions

STX Converta Com

6881041C65 Service Operating Manual

0180305J46 Ear Microphone System and Temple

Transducer CD-ROM



Over 7 million customers have made MyRadioMall.com America's #1 choice when it comes to dependable and reliable Motorola Communications at fantastic prices.

We are now celebrating our 12th year of online service and the best is yet to come.



Advanced Radio Systems, Inc 8726 NW 26 Street #6 Miami, Florida 33172

Voice Numbers: 305-884-1795 *Toll Free:* 1-866-900-Mall (6255) Fax Number: 305-884-1985

12/25/2006